

Declaration of Conformity

Peak Pipe Systems can confirm that our:

- **ClearDuct™ C1+ electric cable ducting range (PE100: CDHKN) 125 – 315mm OD**

are suitable for cable ducting applications, including horizontally directionally drilled duct (HDD). They are designed, manufactured and tested to the following specification:

EN TS 12-24 (Issue 3, July 2014) - Technical specification for plastic ducts for buried electric cables

The full range of products in the table below have been independently approved (witness testing and formal approval) by a representative of a distribution network operator in accordance with the requirements of **EN TS 12-24**, this includes rating of the products with class number “C1+”:

Product	Diameter (mm)	SDR	Tolerance O/D (mm) Minimum	Tolerance O/D (mm) Maximum	Wall Thickness Tolerance (mm) Minimum	Wall Thickness Tolerance (mm) Maximum	Ovality (mm)
CDHKN 125X ***M	125	11	125.0	125.8	10.4	11.4	2.50
CDHKN 160X ***M	160	11	160.0	161.0	13.3	14.5	3.20
CDHKN 180X ***M	180	11	180.0	181.1	15.0	16.4	3.60
CDHKN 200X **M	200	11	200.0	201.2	16.7	18.2	4.00
CDHKN 225X **M	225	11	225.0	226.4	18.8	20.5	4.50
CDHKN 250X **M	250	11	250.0	251.5	20.8	22.7	5.00
CDHKN 280X **M	280	11	280.0	281.7	23.3	25.4	9.80
CDHKN 315X **M	315	11	315.0	316.9	26.3	28.6	11.1

Table 1: Product details

Should you require any further information please do not hesitate to contact us.

For and on behalf of Peak Pipe Systems



.....
 Managing Director of Peak Pipe Systems